

FIN Minimum Contact Disc Conveyors

- **FIN manufactures both idle and motorized heavy-duty disc conveyors.**

Standard features:

- Frame is of steel construction for strength and durability (with optional casters)
- Stainless steel discs are 6" (150 mm) diameter and mounted 5 ½" (120 mm) apart on roller shafts with sealed ball bearings on each end
- Galvanized water tray with drain valve for cleaning discs
- Gravity feed roller shafts
- Feed speed 66 FT/MIN. (motorized version only)



- *Idle system* - 1300 mm x 2500 mm (4' x 8')
- *Idle system* - 1500 mm x 3000 mm (5' x 10')
- *Idle system* - 1500 mm x 3500 mm (5' x 12')

-
- *Motorized system* - 1300 mm x 2500 mm (4' x 8')
 - *Motorized system* - 1500 mm x 3000 mm (5' x 10')
 - *Motorized system* - 1500 mm x 3500 mm (5' x 12')

Options:

- Speed variator (15 to 95 FT/MIN.):
- Four casters:
- Stainless steel water tray:
- Electronic eye stop

Weights:

- *Idle system* - 1300 mm x 2500 mm (4' x 8'): 865 lbs
- *Idle system* - 1500 mm x 3000 mm (5' x 10'): 1000 lbs
- *Idle system* - 1500 mm x 3500 mm (5' x 12'): 1450 lbs
- *Motorized system* - 1300 mm x 2500 mm (4' x 8'): 965 lbs
- *Motorized system* - 1500 mm x 3000 mm (5' x 10'): 1100 lbs
- *Motorized system* - 1500 mm x 3500 mm (5' x 12'): 1550 lbs