

**FIN Pinch Roller**

**CLN 1600 (STANDARD ROLLER)  
CLN 1600 (SEGMENTED ROLLER)**

- Heavy-duty pinch roller with easy and precise hand wheel adjustment for different board thicknesses. Pneumatically adjustable pressure on top roller allows maximum flexibility when working with small or large panels.

**Standard Features:**

- 63" wide
- (2) heavy-duty top and bottom rollers
- Industrial grade construction
- Start and stop buttons, on/off indicator lamp, magnetic start, overload protection with double emergency stop guards
- .5 HP motor, 230/460V 3 Ø
- 145 mm Ø rollers, covered in SHORE 50A rubber, resulting in precise and continuous pressure
- Adjustable air pressure 4 or 8 bar with lever selector
- Maximum opening between rollers: ..... 120 mm (4 ¾")
- Feed speed: ..... 15.2 MT/MIN. (50 FT/MIN.)
- Length of rollers: ..... 1620 mm (63 7/8")
- Rubber on rollers thickness: ..... 9 mm (3/8")
- Rollers diameter: ..... 145 mm
- Chain driven system
- Working height with casters: ..... 930 mm (36 ½")
- Working height without casters: ..... 805 mm (31 ½")
- Air requirements: ..... 110 PSI
- 4 casters
- Net weight: ..... 1200 lbs
- Shipping weight: ..... 1285 lbs
- Crating included

**Options:**

- Spare rollers (**STANDARD**)
- Spare rollers (**SEGMENTED**)
- Single phase motor