
FIN Two Roller Glue Spreader

SC2R

Heavy-duty, two roller glue spreaders with doctor blade and galvanized glue tank.

Standard Features:

- Heavy-duty construction
- Start and stop buttons, on/off indicator lamp, magnetic start, overload protection with double emergency stop bars
- .5 HP motor, 230/460 V 3 Ø
- 185 mm Ø rollers, covered in special anti-acid rubber, precision ground and hard wearing, allowing up to 6 - 7 resurfacings, resulting in precise and uniform spreading of glue
- Special springs on the roller supports allow continuous feed of different panel thicknesses with a variance of up to 5 mm without resetting the machine
- Separate switch allows operator to use 2 rollers together or one at a time
- Self-adjusting chain drive
- 4 casters
- Net weight: 510 - 1200 lbs
- Maximum opening between rollers: 120 mm (4 ¾")
- Feed speed: 19 MT/MIN. (63 FT/MIN.)
- Crating included
- Shipping weight 1300 (51")900 lbs
- Shipping weight 1600 (63")1285 lbs

Sizes (widths) available:

- 300 - 400 - 600 mm (**12" - 16" - 24"**)
- 800 - 1000 (**31" - 39"**)
- 1300 (**51"**)
- 1600 (**63"**)

Options:

- Manual cleaning device
- Automatic cleaning device
- Speed variator, from 15 to 75 FT/MIN
- Spare rollers (**12" - 24"**)
- Spare rollers (**31" - 39"**)
- Spare rollers (**51"**)
- Spare rollers (**63"**)