

---

**FIN Four Roller Glue Spreader**

**SC4/98**

**Heavy-duty, four roller glue spreaders with 2 doctor rollers and galvanized glue tank.**

**Standard Features:**

- Heavy-duty construction
- Start and stop buttons, on/off indicator lamp, magnetic start, overload protection with double emergency stop bars
- Two .9 HP motors, 230/460 V 3 Ø
- 2 spreading rollers 250 mm Ø, covered in special anti-acid rubber, precision ground and hard wearing. Will allow up to 6 - 7 resurfacings.
- 2 ebonite doctor rollers 190 mm Ø allow precise and uniform spreading of glue by rotating at a slower speed than the spreading rollers. When the spreading rollers come in contact with each other, a free wheeling device eliminates overheating and excess wear of the rubber. Accurate dosage is possible by adjusting the distance between the doctor rollers by means of a handwheel and endless screw adjustment.
- Special springs on the roller supports allow continuous feed of different panel thicknesses with a variance of up to 5 mm without resetting the machine.
- Anti-accident devices on the spreading and dosing rollers include double emergency bars (front and back). If the spreading roller and dosing rollers are touching, they will stop when the protection grid is lifted up. If they are not touching each other, they will reverse direction, therefore assuring maximum safety to the operator.
- Separate switch allows operator to use 2 rollers together or one at a time.
- Self-adjusting chain drive
- 4 casters
- Net weight: ..... 2000-2900 lbs
- Maximum opening between rollers: ..... 120 mm (4 ¾")
- Feed speed: ..... 19 MT/MIN. (63 FT/MIN.)
- Crating included

**Sizes (widths) available:**

- 1300 mm (51")
- 1600 mm (63")
- 2000 mm (78")
- 2200 mm (87")

**Options:**

Automatic Cleaning  
Speed Variator with Inverter