

25" Heavy-duty Planer

Model **SP63N with Standard Cutterhead**
Model **SP63N with Tersa Head**

Standard Equipment:

- 12 HP motor for connection at 230/460/3/60
- Magnetic starter with emergency stop
- Electric circuit according to UL specifications
- Overload protection
- 4 table support columns
- Shaving hood
- Digital height display
- 1 motorized bed roller
- 1 outfeed roller
- Sectional infeed roll and chipbreaker
- Motorized table raising and lowering
- Set of 4 knives mounted
- Service tools

Optional Equipment:

- Knife grinder attachment
- Set of 4 HSS knives
- Set of four knives for Tersa head
- Variable infeed speed
- Electronic table positioning

Specifications:

- Table dimensions:24 ¾ x 46"
- Width of stock (maximum): 24 ¾"
- Thickness of stock (maximum): 12 ¼"
- Thickness of stock (minimum): 1/8"
- Depth of cut (maximum): 5/16"
- Minimum length (unbutted): 10"
- Rate of feed--variable:18 – 60 FT/min.
- Number of knives on cutterhead: 4
- Diameter of cutterhead: 4 ¾"
- Cutterblock speed: 5000 rpm
- Spiral infeed (*positioned directly above bedrolls*): Sectional
- Outfeed: Motorized floating solid roller

Overall Dimensions:

- Net weight: 1764 LBS.
- Gross weight: 1940 LBS.
- Packing size: 50" x 46" x 53"

Electrical Requirements: 42.5 AMPS at 230 V

Dust Collector Requirements: 980 CFM

dB Level: 76.7